Acer **P**3250









ColorBoost II SmartFormat EcoProjection

Weighing only 1.2 kg (2.7 lbs.), the P3250 projector is an ultra-lightweight powerhouse casting 2000 ANSI Lumens brightness, and boasting native XGA (1024 x 768) resolution and 2000:1 contrast ratio for high-impact projection performance in presentation venues of

different sizes.

An HDMITM port offers advanced digital connectivity to a variety of media sources. Acer ColorBoost II and SmartFormat technologies provide brilliant, professional imaging for superior enterprise-level presentations. With Acer EcoProjection technology, the P3250 saves energy by cutting standby power by as much as 50 percent.

High-impact performance to go



































Feature highlights Dazzling views, portable design Unique, elegant design Acer ColorBoost II technology XGA resolution DLP system design Earth-friendly, dynamic functionality Acer EcoProjection technology Longer lamp life (5000 hours) ECO mode Acer Instant Pack technology Automatic safety shutdown Digital zoom and pan

- Windows Vista® compliance
 Empowering usability, versatile connectivity
 Acer Empowering Technology
 o Acer ePower Management with High Altitude Mode
 o Acer eView Management with innovative Blackboard Mode
 o Acer eTimer Management
 o Acer eOpening Management
 Acer SmartFormat technology
 Keystone correction (40° vertical)
 Quick start
 Ouick signal detection

Acer Projector P3250 Quick Spec

Projection system	DLP®
Resolution	Native: XGA (800 x 600)
	Maximum: SXGA (1,600 x 1,200),
	WXGA+ (1,680 x 1,050)
Aspect ratio	4:3 (native), 16:9
Contrast ratio	2000:1
Displayable colors	134 million colors
Brightness	2000 ANSI Lumens
Projection distance	3.3 - 39 feet (1.0 - 11.9 m)
Throw ratio	50 inches @ 2m(1.95 ~ 2.15:1)
Lamp Type	Osram 165 W user replaceable P-VIP lamp
Lamp life	5,000 Hours
Keystone correction	±40 degrees (vertical)
Projection mode	Front, rear, front-ceiling, rear-ceiling
Ceiling mount capability	
Weight	2.7 lbs (1.2 Kg)
Dimensions (W x H x D)	210 x 165 x 64 mm (8.3" x 6.5" x 2.5")
Remote Control	IR remote control with laser pointer &
	PgUp/PgDn functions
Noise level	29 dBA





















